

NIKKEN eu



PROFESSIONAL SHRINK FIT MACHINE

Fully automatic shrinking and cooling

PROFESSIONAL SHRINK FIT MACHINE

Fully automatic shrinking and cooling

- Quick change coil system
- Improved drying feature after the cooling process
- Ergonomic working height 1300 mm
- Fully automatic cooling and drying of the shrink chuck



	ISG3410WK4-11-WS-BIL
Ident No.	5072341
Control Panel	Graphical
Clamping Range SC	3-50mm
Clamping Range HSS	6-50mm
Coil	quick change system, expandable upto 50mm* 4 pole disks
Max. tool length	680mm bei at HSK-A63
Max-Cooling Length	400mm bei at HSK-A63
Cooling Type	Liquid cooling with drying, geometry independent
Cooling time	20s/50 L
Max. machine interface	HSK-A100 SK50
Power	11kW
Electric current supply	400V /16A / 50Hz
Air Pressure	4 Bar
Dimensions	800 x 560 x 1950mm
Delivery Package:	incl. Coil 1 form 3-32mm, 4 pole discs, 1000ml cooling and corrosion protection, protective gloves and operation manual, without tool holder/cooling adaptors

*THD Chuck up to max. 25mm only with Coil Ident No. 5129760

Extras

Code	Product	Features
ISGZ3410-TOUCH-BF	Touch screen system with auto software	Standard
T3-WWKL-HSK63 tool carrier	HSK63 adapter	Optional
T3-WWKL-SK40 tool carrier	SK40 adapter	Optional